

InPro 3250 (i) Highest Performance, Highest Accuracy



InPro 3253

InPro 3250i

Features Overview

- Fully autoclavable or sterilizable in-situ (InPro 3250 (i), InPro 3253 (i))
- Pressurized electrolyte reduces maintenance
- MaxCert™, including biocompatibility according to USP 26, Chapter 27

The InPro 3250 (i) family is a pre-pressurized, liquid-filled, low-maintenance pH sensor and temperature sensor for in-line measurements in demanding applications. Its durable design is well suited for harsh chemical process conditions or to meet the stringent demands of sterile biotech applications where CIP and SIP are used. These rugged electrodes lead the industry for fast and precise measurements, even after repeated autoclaving or sterilization cycles at 140 °C (284 °F). The InPro 3250 (i) family is available with an expanded selection of different pH-sensitive glass membranes. This guarantees the best possible measurement performance under the most diverse operating conditions, both in chemical and biotech processes. The platinum-auxiliary electrode (solution ground) which functions to eliminate ground loop problems, allows for use of advanced sensor diagnostics, or can be used as an ORP (redox) sensor. Also available with Intelligent Sensor Management (ISM) for Plug and Measure and advanced diagnostics.

Specifications

pH range	0–14 pH InPro 3250 (i); 0–12 pH InPro 3253 (i); 1–11 pH InPro 3251 (i), InPro 3252
Temperature	0 to 100 °C (32 to 212 °F) InPro 3250 (i), InPro 3253 (i); –25 to 80 °C (–13 to 176 °F) InPro 3251 (i); 0 to 80 °C (32 to 176 °F) InPro 3252
Operating pressure	0 to 4 barg (0 to 58 psig)
Cable connection	ISM: KS8; Analog: VP
Process connection	Pg 13.5 thread
Reference system	Argentinal with silver-ion trap
Type of junction	Ceramic junction
Reference electrolyte	Pre-pressurized liquid
Lengths	120 mm, 225 mm, 325 mm, 425 mm
Shaft diameter	12 mm
Temperature sensor	ISM: digital Analog: Pt 100 or Pt 1000
Sterilizable	Yes, up to 140 °C (284 °F)
Autoclavable	Yes
pH membrane	Various by applications

Certificates and Approvals METTLER TOLEDO Quality Certificate, Pressure Equipment Directive guidelines (PED) 97/23/EC, ATEX: Ex ia IIC T6/T5/T4/T3 Ga/Gb, FM: IS Cl. I, II, III, Div 1, GR ABCDEFG/T6

Intelligent Sensor Management (ISM)

pH electrodes with integrated ISM functionality allow Plug and Measure and advanced diagnostics. ISM simplifies the installation, handling and maintenance of measurement equipment. For more information see ISM introduction pages 12–13.

► www.mt.com/InPro3250

Ordering Information

ISM Electrodes	Length	Temp. Signal	Order Number		
– with alkali resistant glass					
InPro 3250i/SG	120 mm	Digital	52 005 373		
InPro 3250i/SG	225 mm	Digital	52 005 374		
InPro 3250i/SG	325 mm	Digital	52 005 375		
InPro 3250i/SG	425 mm	Digital	52 005 376		
– for applications at low temperatures					
InPro 3251i/SG	120 mm	Digital	52 003 693		
– with steam sterilizable glass					
InPro 3253i/SG	120 mm	Digital	52 005 377		
InPro 3253i/SG	225 mm	Digital	52 005 378		
InPro 3253i/SG	325 mm	Digital	52 005 379		
InPro 3253i/SG	425 mm	Digital	52 005 380		
Analog Electrodes	Length	Temp. Signal	Order Number	Temp. Signal	Order Number
– with alkali resistant glass					
InPro 3250	120 mm	Pt 100	52 002 547	Pt 1000	52 002 548
InPro 3250	225 mm	Pt 100	52 002 552	Pt 1000	52 002 553
InPro 3250	325 mm	Pt 100	52 002 554	Pt 1000	52 002 555
InPro 3250	425 mm	Pt 100	52 002 556	Pt 1000	52 002 557
InPro 3250SG	120 mm	Pt 100	52 002 558	Pt 1000	52 002 559
InPro 3250SG	225 mm	Pt 100	52 002 560	Pt 1000	52 002 561
InPro 3250SG	325 mm	Pt 100	52 002 562	Pt 1000	52 002 563
InPro 3250SG	425 mm	Pt 100	52 002 564	Pt 1000	52 002 565
– for applications at low temperatures					
InPro 3251	120 mm	Pt 100	52 002 585	–	–
InPro 3251	225 mm	Pt 100	52 002 586	–	–
– for applications in hydrofluoric acid cont. media					
InPro 3252	120 mm	Pt 100	52 002 587	–	–
InPro 3252	225 mm	Pt 100	52 002 588	–	–
InPro 3252	250 mm	Pt 100	52 002 589	–	–
– with steam sterilizable glass					
InPro 3253	120 mm	Pt 100	52 002 566	Pt 1000	52 002 567
InPro 3253	225 mm	Pt 100	52 002 568	Pt 1000	52 002 569
InPro 3253	250 mm	Pt 100	52 002 570	–	–
InPro 3253	325 mm	Pt 100	52 002 571	Pt 1000	52 002 572
InPro 3253	425 mm	Pt 100	52 002 573	Pt 1000	52 002 574
InPro 3253SG	120 mm	Pt 100	52 002 576	Pt 1000	52 002 577
InPro 3253SG	225 mm	Pt 100	52 002 578	Pt 1000	52 002 579
InPro 3253SG	325 mm	Pt 100	52 002 580	Pt 1000	52 002 581
InPro 3253SG	425 mm	Pt 100	52 002 582	Pt 1000	52 002 583



InPro Sensor Designation

The last digit of the InPro designation indicates the

pH glass type:

00: High alkali glass (HA)

01: Low temperature glass (LoT)

02: Hydrofluoric acid resistant glass (HF)

03: Steam sterilizable glass (A41)

Suitable Housings	p.
InFit 761e	140
InFit 762e	142
InFlow	146
InDip	148
InTrac 777e	152
InTrac 797e	154
InTrac 781	156
InTrac 785/787	158